

EC Thermal Receipt Printer



EC-PM-X30



Features

- 58mm/80mm/82.5mm paper width available
- IAP function supports firmware update within 5S
- Emulation Driver ESC/POS Windows/ JPOS/Linux/ Android/Mac
- Metallic frame mechanism

Specifications

Print method	Direct thermal
Print width	79.5±0.5mm
Print speed	300mm/s
Paper thickness	0.06~0.08mm
Interface	USB+ Lan/USB+Serial / USB+Serial+Bluetooth / USB+ Serial+ Wifi
Column capacity	576 dots/line(adjustable by command)
Character size	ANK, Font A: 1.5 x 3.0mm (12x2 4 dots) Font B: 1.1x2.1mm(9x17 dots) Chinese, traditional Chinese :3.0 x 3.0mm(2 4 x2 4 dots)
Bar code	UPC-A/UPC-E/ JAN13(EAN13)/ JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 QR CODE 、 PDF417
Code page	PC34 7(Standard Europe)/ Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII /Latvian/ Arabic/ PT151(1251)
Auto Cutter	Partial
Cutter life	2 million cuts
Print head life	150KM
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC220V, 50~60Hz
Power source	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0~45%, Humidity: 10~80%
Storage environment	Temperature: -10~60%, Humidity: 10~90%
Weight	1.115 kg
Dimension (DxWxH)	133x126x130mm(WxDxH)

*All rights reserved. All specifications are subject to change without notice. 保留隨時更改本文中產品相關描述之權利。若有更改恕不另行通知。

Asia, Pacific & Europe: Unit A, 2/F., Mai Tak Industrial Building #221 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Tel: (852) 3590 6397 | Fax: (852) 3590 6497 | www.eclinepos.com | sales@ecline.com.hk

México, E.U.A, Latinoamérica: Nueva Irlanda #4057, Fracc. Industrial Lincoln, C.P. 64310, Monterrey, N.L. México.
+52 (81) 8370-5096 | 01 800 509-1818 | www.eclinepos.com | ventas@ecline.com.mx